

3 Polyethylene Tape (Clear) 3K10

Technical Data

June, 2002

Product Description A polyethylene tape with a very low-tack adhesive system to help protect many polished metals, plastic and glass materials.

Construction

Backing	Low-density polyethylene
Adhesive	Acrylic
Color	Clear
Standard Roll Size	1220mm x 100m

Physical Properties The following technical information and data should be considered or typical only and should not be used for specification purposes.

ASTM Method

Adhesion to Steel:	60 g/in. width	D-3330
Tensile Strength: (Break or Yield)	Min 1.4 kg/in. width	D-3759
Elongation at Break: (Break or Yield)	Min 160 %	D-3759
Total Thickness:	0.065 mm	D-3652

General Information 3K10 tape can help protect many plastics and glass materials with minimum adhesion build-up and clean removal. For optimum performance, 3M Protective Tape should be applied and removal at a temperature not less than 16°C.

Polyethylene Tape (Clear)

3K10

Application Ideas Protection of ...

Backlight unit of LCD

Polished, molded plastic materials

High-gloss screen printed nameplates.

Gloss instrument clusters.

Important Notice

3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of a 3M ITSD product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M ITSD product. Given the variety of factors that can affect the use and performance of a 3M ITSD product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M ITSD product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Limitation of Remedies and Liability

If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF, OR TO REPAIR OR REPLACE, THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for any loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.
