

PRODUCT INFORMATION 3M Stationery and Office Supplies Division



Scotch™ No. 810 Magic™ Tape

DESCRIPTION:

A tape that is frosty in appearance on the roll, yet invisible on most paper.

CHARACTERISTICS:

Backing:	Matte acetate.
Adhesive:	Synthetic.
Adhesion to Steel:	25 oz./in. width.
Tensile Strength:	15 lbs./in. width.
Elongation at Break:	15%.
Total Thickness:	2.5 Mills.

FEATURES	ADVANTAGES	BENEFITS
Synthetic adhesive	Aggressive adhesion to a variety of surfaces.	Eliminates need for multiple tapes for the office, saving money.
	Extremely long aging, non-yellowing.	Saves time and money because it eliminates reapplication.
	Resists discoloration.	Eliminates reapplication, thus saves time and money.
Matte Acetate.	Moisture resistant.	Won't destroy repaired papers, makes job easier and saves time.
	Write-on surface. Can be written on with pencil, pen, and other writing device.	Saves time and makes job easier when markovers or labels are needed.
	Invisible on the job, appearance of papers mended are not altered.	Easier reading and reproducing; makes job easier and saves time.
	Light diffusing, resists shadowing during dry copying.	Saves time and makes job easier because it allows reproducing.
Release coating	Low (easy) unwind.	No roll breakage, thus makes job easier.
Plastic core	Clean Appearance. Fragments on edge of roll.	Eliminates paper

IMPORTANT NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and, except where prohibited by law, the following is made in lieu of all express or implied rights, warranties and conditions, statutory or otherwise: Seller's and manufacturer's only obligation shall be to repair or replace, at manufacturer's option, such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable in Contract or in Tort, for any injury, loss or damage, direct, indirect, incidental, special or consequential, (including, without limitation, lost profits, goodwill, or business opportunity) arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by offices of seller and manufacturer. Since the manufacturer of the product described in this document has no means of controlling the final use of the product by the consumer or user, it is the responsibility of the immediate purchaser and any intermediate seller(s) to inform the user of the purposes for which the product may be fit and suitable and of the properties of the product, including the precautionary measures which must be taken in order to ensure the safety of the users and of other third persons and property.

3

3M Canada Company
Post Office Box 5757
London, Ontario N6A 4T1

APPLICATIONS:

1. Mending tracings, drawings, library books, blueprints, legal documents, securities, and other permanent type applications. The matte backing will blend in with the paper and the adhesive will not affect most papers.
2. Commonly used in offices, drafting, and engineering departments. Will not affect blueprint reproductions.
3. Using as a carrier or for a covering over transfer letters to protect them from "scuffing."
4. Assembling V-Grooves and Inlay Mats in picture framing.

上海雅制行实业有限公司
如需原件本公司
请致电本公司